

illume™



Better than a Skylight

Simulating the outside, inside your home



PATENTED
TECHNOLOGY



AMBIENT LIGHT
TECHNOLOGY





See the difference illume can make to your home or work space!

The illume Skylight Alternative has a sleek design, using solar technology to transform any room into a bright space by simulating the lighting conditions outside, without the need for a light shaft.

Install an illume, instead of a traditional skylight, to bring more light into your home. Perfect for walk-in robes, enclosed hallways, kitchens, pantries and even your bathroom.

Unlike a traditional skylight you can even install an illume to lower levels, basements and attics – the possibilities are endless! illume's innovative design cuts the cost of your electricity, with no running costs or batteries.

Installation is easy and non intrusive. Unlike traditional skylights, there is no light shaft, and penetration is not required.



No bugs



No leaks



No heat transfer



No light shaft

- No light shaft or UV
- No mains power or batteries required
- No running costs
- Easy to install
- Hail resistant
- 2 year warranty (upon registration)
- IC-4 Rating


How does illume work?



Solar Panel

illume is powered by a solar panel positioned on the roof, cutting the cost of your power bill, by reducing the need for electrical lighting or batteries in your homes dark rooms or spaces.

illume Skylight Alternative



Transfer Cable

The solar power is transferred to the light panel via a cable, simulating the lighting conditions outside. illume automatically comes to life at sunrise, and its intensity varies during the day depending on sun exposure and cloud cover outside.



illume Light Panel

The lighting panel uses **Ambient Light Technology (A.L.T)**, bringing light into the dark areas of your home, creating the feeling of harmony between external and internal lighting conditions.

Accessories and Options



illume Remote Dimmer

- Turn your illume on/off remotely
- Automatically resets overnight

Suits all illume sizes except 600x1200mm



Multi System

- Up to 9 illume light panels can be connected to 1 solar panel
- Perfect for multi storey buildings






Interior Window

- Solution to a common construction limitation
- Perfect for boundary walls



illumeskylights.com.au

Specifications



CODE	SIZE	LUMENS*	STYLE	IDEAL AREA	MOUNTING TYPE
KIS1010	180mm	540lm	Round	2m2	Flush
KIS1012	270mm	1050lm	Round	6m2	Flush
KIS1014	350mm	1650lm	Round	10m2	Flush
KIS2010	300mm	720lm	Square	5m2	Flush
KIS2012	400mm	1050lm	Square	7m2	Flush

Premium Range

CODE	SIZE	LUMENS*	STYLE	IDEAL AREA	MOUNTING TYPE
KIS1013TA	280mm	1560lm	Round	7m2	Flush
KIS1014TA	350mm	2100lm	Round	11m2	Flush
KIS1014TAS	350mm	2100lm	Round	11m2	Surface
KIS2010TA	300mm	1050lm	Square	6m2	Flush
KIS2010TAS	300mm	1050lm	Square	6m2	Surface
KIS2012TA	400mm	1420lm	Square	9m2	Flush
KIS2012TAS	400mm	1420lm	Square	9m2	Surface
KIS2014TA	500mm	1950lm	Square	11m2	Flush
KIS2014TAS	500mm	1950lm	Square	11m2	Surface
KIS2016TA	600mm	2250lm	Square	13m2	Flush
KIS2016TAS	600mm	2250lm	Square	13m2	Surface
KIS2017TA	700mm	2530lm	Square	17m2	Flush
KIS2017TAS	700mm	2530lm	Square	17m2	Surface
KIS3012TA	300 x 600mm	1500lm	Rectangle	10m2	Flush
KIS3012TAS	300 x 600mm	1500lm	Rectangle	10m2	Surface
KIS3018TA	600 x 900mm	3300lm	Rectangle	20m2	Flush
KIS3018TAS	600 x 900mm	3300lm	Rectangle	20m2	Surface
KIS3014TA	300 x 1200mm	3300lm	Rectangle	20m2	Flush
KIS3014TAS	300 x 1200mm	3300lm	Rectangle	20m2	Surface
KIS3020TA	400 x 1200mm	3630lm	Rectangle	24m2	Flush
KIS3020TAS	400 x 1200mm	3630lm	Rectangle	24m2	Surface

*Maximum brightness and lumen value based on

Available in a range of shapes and sizes, there is the perfect illume for every room.
Visit the website for more information and mounting options.

